

Appl. No. 10/608,176  
Amdt. Dated June 19, 2006  
Reply to Office Action of March 17, 2006

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the above-identified application:

1. (original) A preload adjustment device, the preload adjustment device comprising:
  - a) a piezodynamic preload spacer, the piezodynamic preload spacer coupled to a bearing in a momentum control device, the piezodynamic preload spacer configured such that an application of a control voltage to the piezodynamic preload spacer causes a change in a dimension of the piezodynamic preload spacer, and wherein the piezodynamic preload spacer is configured such that a change in the dimension of the piezodynamic preload spacer changes a preload of the bearing; and
  - b) a control system, the control system providing selective control of the control voltage to selectively control the preload on the bearing.
2. (original) The preload adjustment device of claim 1 wherein the piezodynamic preload spacer is located adjacent the bearing.
3. (original) The preload adjustment device of claim 1 wherein the bearing comprises a duplex bearing pair and wherein piezodynamic preload spacer is located between the duplex bearing pair.

Appl. No. 10/608,176  
Amdt. Dated June 19, 2006  
Reply to Office Action of March 17, 2006

4. (currently amended) The preload adjustment device of claim 1 wherein piezodynamic preload spacer comprises a ring shaped spacer having a thickness, and wherein the application of the control voltage to the piezodynamic preload spacer causes a change in the thickness.
5. (original) The preload adjustment device of claim 1 wherein the piezodynamic preload spacer comprises a piezoelectric material.
6. (withdrawn) The preload adjustment device of claim 1 wherein the piezodynamic preload spacer is coupled to the bearing through an intermediate member.
7. (original) The preload adjustment device of claim 1 wherein the momentum control device comprises a reaction wheel.
8. (original) The preload adjustment device of claim 1 wherein the momentum control device comprises a control moment gyroscope.

Appl. No. 10/608,176  
Amdt. Dated June 19, 2006  
Reply to Office Action of March 17, 2006

9. (original) The preload adjustment device of claim 1 wherein the control system provides selective control of the control voltage to control the preload to compensate for changes in operating environment.
10. (original) The preload adjustment device of claim 1 wherein the control system provides selective control of the control voltage to control the preload to compensate for wear in the bearing.
11. (original) The preload adjustment device of claim 1 wherein the control system provides selective control of the control voltage to control the preload to compensate for thermal expansion in the bearing.
12. (original) The preload adjustment device of claim 1 wherein the control system provides selective control of the control voltage to distribute lubrication in the bearing.
13. (original) The preload adjustment device of claim 12 wherein the control system provides a varying control voltage to distribute the lubrication in the bearing.

Appl. No. 10/608,176  
Amdt. Dated June 19, 2006  
Reply to Office Action of March 17, 2006

14. (original) The preload adjustment device of claim 1 wherein the control system increases preload during a launch of the momentum control device into space.

15. (original) The preload adjustment device of claim 1 wherein the piezodynamic preload spacer is configured to provide a reduced preload with a low control voltage and an increased preload with a high control voltage.

16. (original) The preload adjustment device of claim 15 wherein the reduced preload comprises an optimal operating preload.

17. (original) A preload adjustment device for adjusting preload in a duplex bearing in a momentum control device, the duplex bearing including a first bearing race and a second bearing race, the preload adjustment device comprising:

- a) a piezodynamic preload spacer, the piezodynamic preload spacer coupled between the first bearing race and the second bearing race, the piezodynamic preload spacer configured such that an application of a control voltage to the piezodynamic preload spacer causes a change in a dimension of the piezodynamic preload spacer, and wherein the piezodynamic preload spacer is configured such that a change in the dimension of the piezodynamic preload spacer changes the preload of the duplex bearing; and

Appl. No. 10/608,176  
Amdt. Dated June 19, 2006  
Reply to Office Action of March 17, 2006

- b) a control system, the control system providing selective control of the control voltage to selectively control the preload on the bearing.

18. (original) The preload adjustment device of claim 17 wherein piezodynamic preload spacer comprises a ring shaped spacer having a thickness, and wherein the application of the control voltage to the piezodynamic preload spacer causes a change in thickness.

19. (original) The preload adjustment device of claim 17 wherein the control system provides selective control of the control voltage to control the preload to compensate for changes in operating environment.

20. (original) The preload adjustment device of claim 17 wherein the control system provides selective control of the control voltage to control the preload to compensate for wear in the bearing.

21. (original) The preload adjustment device of claim 17 wherein the control system provides selective control of the control voltage to control the preload to compensate for thermal expansion in the bearing.

**Appl. No. 10/608,176**

**Amdt. Dated June 19, 2006**

**Reply to Office Action of March 17, 2006**

**22.(original) The preload adjustment device of claim 17 wherein the control system provides a varying of the control voltage to distribute lubrication in the bearing.**

**23.(original) The preload adjustment device of claim 17 wherein the control system increases preload during a launch of the momentum control device into space.**

**24.(original) The preload adjustment device of claim 17 wherein the piezodynamic preload spacer is configured to provide an optimal operating preload for operating in space with a low control voltage and an increased preload with a high control voltage.**

Appl. No. 10/608,176

Amdt. Dated June 19, 2006

Reply to Office Action of March 17, 2006

25. (withdrawn) A lubrication distribution device for distributing lubrication in a bearing in a momentum control device, the lubrication distribution device comprising:

- a) a piezodynamic spacer, the piezodynamic spacer coupled to the bearing in the momentum control device, the piezodynamic spacer configured such that an application of a control voltage to the piezodynamic spacer causes a change in a dimension of the piezodynamic spacer, and wherein the piezodynamic spacer is configured such that a change in the dimension of the piezodynamic spacer changes exerts a force on the bearing; and
- b) a control system, the control system varying the control voltage to provide a periodic force on the bearing and distribute lubrication in the bearing.

26. (withdrawn) The lubrication distribution device of claim 25 wherein the piezodynamic spacer exerts a force on the bearing that that changes a preload on the bearing.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**